

REPLACING PILE BRUSH

INSTRUCTIONS

1

Retract shade to upper limit.

2

Remove snap cover from one side track and uninstall the track.

3

Lower shade to chest height or a comfortable height to reach the hem bar.

4

Remove silver screws from the top and bottom of the hem bar keeping plastic caps in place. Remove screws from one side of the fabric only, front or back.

5

Remove the two silver through bolts running horizontally through hem bar caps and fabric. There are small nuts used on the back side, be careful not to drop them as bolts are removed.

6

Remove half of the hem bar cap in which you took the silver screws out in step 4.

7

Slide the existing pile brush by pulling it horizontally toward the open end of the hem bar.

8

Cut new pile brush to the same size as the old brush and reinsert it in the same groove in which the old brush was removed. Be sure the new pile brush is seated fully in the groove and is the full length of the hem bar including plastic caps.

9

Reinstall the half of the hem bar cap that was removed in step 6.

10

Reinsert the silver through bolts and nuts horizontally that were removed in step 5. Ensure the top screw runs through the hole in the fabric the same way it was before it was removed. Be careful not to over tighten the horizontal screws so that they protrude out of the back of the cap.

11

Reinstall the two silver screws in the top and bottom of the hem bar removed in step 4.

12

Retract shade to its upper limit and reinstall the track per original installation instruction.

13

Follow the original installation instruction to ensure proper operation of the shade.

14

Limits may need to be adjusted for optimal seal with new pile brush.